



BARGE "GONSOU LIN - 206"

LE BEOUF BROTHERS

HULL NO. 4389

CORRECTION TABLE FOR TRIM AFT.

FOR INNAGE GAUGES ONLY

TRIM	TANKS NO. 1 PORT OR STAR.	TANKS NO. 2 PORT OR STAR.	TANKS NO. 3 PORT OR STAR.
0'-6"	(-) 0' - 0 3/4"	(-) 0' - 1"	(+) 0' - 0 3/4"
1'-0"	(-) 0' - 1 5/8"	(-) 0' - 1 7/8"	(+) 0' - 1 5/8"
1'-6"	(-) 0' - 2 3/8"	(-) 0' - 2 7/8"	(+) 0' - 2 1/2"
2'-0"	(-) 0' - 3 1/4"	(-) 0' - 3 3/4"	(+) 0' - 3 1/4"
2'-6"	(-) 0' - 4"	(-) 0' - 4 3/4"	(+) 0' - 4 1/8"
3'-0"	(-) 0' - 4 7/8"	(-) 0' - 5 3/4"	(+) 0' - 4 7/8"
3'-6"	(-) 0' - 5 5/8"	(-) 0' - 6 5/8"	(+) 0' - 5 3/4"
4'-0"	(-) 0' - 6 1/2"	(-) 0' - 7 5/8"	(+) 0' - 6 5/8"
4'-6"	(-) 0' - 7 1/4"	(-) 0' - 8 1/2"	(+) 0' - 7 3/8"
5'-0"	(-) 0' - 8 1/8"	(-) 0' - 9 1/2"	(+) 0' - 8 1/4"

NOTE: FOR TRIM FWD., REVERSE SIGNS.

NOTE: IF LIQUID SURFACE TOUCHES TANK BOTTOM OR DECK WHEN GAUGED,
TRIM CORRECTIONS ARE NOT ACCURATE.

NOTE: FOR "OUTAGE" GAUGES, REVERSE SIGNS.

DATE: 5/22/01

BY:


INSPECTORATE AMERICA CORPORATION



BARGE "GONSOULIN - 206" LE BEOUF BROTHERS

INNAGE TABLE

2 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 4389

Table with columns for depth (0 FT. to 14 FT.) and corresponding capacity values in barrels. Includes a note: CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 5/22/01

REFERENCE GAUGE HEIGHT : 15'-9 1/4 (RIM OF 2" DIA. BALL VALVE LOCATED NEAR AFT. BULKHEAD)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation signature and logo



BARGE "GONSOULIN - 206" LE BEOUF BROTHERS

INNAGE TABLE

3 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 4389

IN	0 FT.	IN	1 FT.	IN	2 FT.	IN	3 FT.	IN	4 FT.	IN	5 FT.	IN	6 FT.	IN	7 FT.	IN	8 FT.	IN	9 FT.	IN	10 FT.	IN	11 FT.	IN	12 FT.	IN	13 FT.	IN	14 FT.
0	SUMP 0.27	0	273.97	0	610.83	0	947.70	0	1,284.56	0	1,621.43	0	1,958.29	0	2,295.15	0	2,632.02	0	2,968.88	0	3,293.58	0	3,496.61	0	3,693.24	0	3,888.17	0	4,083.10

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 5/22/01

REFERENCE GAUGE HEIGHT : 15'-9 1/2" (RIM OF 2" DIA. BALL
VALVE LOCATED NEAR FWD. BULKHEAD)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE
IN ACCORDANCE WITH APPLICABLE API STANDARDS AND
ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION