



BARGE "GONSOULIN - 503"
LE BEOUF BROTHERS

INNAGE TABLE

1 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 4

Table with 14 columns representing gauge heights from 0 FT. to 14 FT. Each column contains multiple rows of capacity data for different barge configurations.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 12/16/08

15 FT 5,280.86

* CAPACITY BELOW STRIKE POINT.

PORT REFERENCE GAUGE HEIGHT : 18'-4 3/4" (TO RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STAR REFERENCE GAUGE HEIGHT : 18'-4 1/2" (TO RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature

INSPECTORATE AMERICA CORPORATION



**BARGE "GONSOU LIN - 503"
LE BEOUF BROTHERS**

2 PORT OR STAR

INNAGE TABLE

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 4

IN	0 FT.	IN	1 FT.	IN	2 FT.	IN	3 FT.	IN	4 FT.	IN	5 FT.	IN	6 FT.	IN	7 FT.	IN	8 FT.	IN	9 FT.	IN	10 FT.	IN	11 FT.	IN	12 FT.	IN	13 FT.	IN	14 FT.			
0	22.81	0	355.05	0	715.48	0	1,075.66	0	1,435.26	0	1,795.41	0	2,155.55	0	2,515.70	0	2,875.84	0	3,235.98	0	3,596.13	0	3,956.27	0	4,316.42	0	4,674.78	0	5,019.81			
10	294.98	10	655.41	10	1,015.76	10	1,375.24	10	1,735.38	10	2,095.53	10	2,455.67	10	2,815.82	10	3,175.96	10	3,536.10	10	3,896.25	10	4,256.39	10	4,616.53	10	4,976.67	10	5,286.65			
11	325.01	11	685.44	11	1,045.71	11	1,405.25	11	1,765.40	11	2,125.54	11	2,485.68	11	2,845.83	11	3,205.97	11	3,566.11	11	3,926.26	11	4,286.40	11	4,646.54	11	4,991.54	11	5,274.16			
12	340.03	12	700.46	12	1,060.68	12	1,420.26	12	1,780.40	12	2,140.55	12	2,500.69	12	2,860.83	12	3,220.98	12	3,581.12	12	3,941.27	12	4,301.41	12	4,661.55	12	5,006.74	12	5,275.41			
13	347.54	13	707.97	13	1,068.17	13	1,427.76	13	1,787.91	13	2,148.05	13	2,508.19	13	2,868.34	13	3,228.48	13	3,588.63	13	3,948.77	13	4,308.91	13	4,669.05	13	5,014.24	13	5,276.04			
																															15 FT	5,276.66

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 12/16/08

* CAPACITY BELOW STRIKE POINT.

REFERENCE GAUGE HEIGHT : 18'-5 1/4" (TO RIM OF 2" DIA. BALL VALVE
LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE
IN ACCORDANCE WITH APPLICABLE API STANDARDS AND
ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

(Signature)
INSPECTORATE AMERICA CORPORATION



BARGE "GONSOU LIN - 503" LE BEOUF BROTHERS

INNAGE TABLE

3 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 4

Table with 15 columns representing 0 FT. to 14 FT. and 3 rows per column representing different measurement points. Includes capacity values in barrels of 42 U.S. gallons.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 12/16/08

* CAPACITY BELOW STRIKE POINT.

PORT REFERENCE GAUGE HEIGHT: 18'-5" (TO RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STAR REFERENCE GAUGE HEIGHT: 18'-4 3/4" (TO RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature

INSPECTORATE AMERICA CORPORATION



BARGE "GONSOULIN - 503" LE BEOUF BROTHERS

OUTAGE TABLE

1 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 4

0 FT.		1 FT.		2 FT.		3 FT.		4 FT.		5 FT.		6 FT.		7 FT.		8 FT.		9 FT.		10 FT.		11 FT.		12 FT.		13 FT.		14 FT.	
IN	OUT	IN	OUT	IN	OUT	IN	OUT	IN	OUT	IN	OUT	IN	OUT	IN	OUT	IN	OUT	IN	OUT	IN	OUT	IN	OUT	IN	OUT	IN	OUT	IN	OUT
0		0		0		0		0	5,149.31	0	4,810.05	0	4,455.61	0	4,094.99	0	3,734.36	0	3,373.74	0	3,013.11	0	2,652.49	0	2,291.87	0	1,931.24	0	1,570.62

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 12/16/08

REFERENCE GAUGE HEIGHT : 18'-4 1/2" (TO RIM OF 2" DIA. BALL VALVE
LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE
IN ACCORDANCE WITH APPLICABLE API STANDARDS AND
ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION



BARGE "GONSOULIN - 503" LE BEOUF BROTHERS

OUTAGE TABLE

2 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 4

Table with columns for height (0 FT. to 14 FT.) and multiple rows of capacity data (0 to 14 ft. in 1/4, 1/2, 3/4 increments).

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 12/16/08

REFERENCE GAUGE HEIGHT : 18'-5 1/4" (TO RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature and INSPECTORATE AMERICA CORPORATION logo.



BARGE "GONSOULIN - 503" LE BEOUF BROTHERS

OUTAGE TABLE

3 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 4

	15 FT.	16 FT.	17 FT.	18 FT.	19 FT.	20 FT.	21 FT.	22 FT.	23 FT.	24 FT.	25 FT.	26 FT.	27 FT.	28 FT.	29 FT.
0	1,220.54	859.99	498.79	140.60											
1/4	1,213.04	852.47	491.27	133.25											
1/2	1,205.53	844.94	483.74	125.90											
3/4	1,198.03	837.42	476.22	118.56											
1	1,190.52	829.89	468.69	111.21											
1/4	1,183.02	822.37	461.17	103.86											
1/2	1,175.52	814.84	453.64	96.51											
3/4	1,168.01	807.32	446.12	89.16											
2	1,160.51	799.79	438.59	82.44											
1/4	1,153.00	792.27	431.07	75.72											
1/2	1,145.50	784.74	423.54	69.00											
3/4	1,138.00	777.22	416.02	62.28											
3	1,130.49	769.69	408.49	56.81											
1/4	1,122.99	762.17	400.97	51.35											
1/2	1,115.48	754.64	393.44	45.88											
3/4	1,107.98	747.12	385.92	40.41											
4	1,100.48	739.59	378.39	36.02											
1/4	1,092.97	732.07	370.87	31.63											
1/2	1,085.47	724.54	363.34	27.24											
3/4	1,077.96	717.02	355.82	22.85											
5	1,070.46	709.49	348.29												
1/4	1,062.96	701.97	340.77												
1/2	1,055.45	694.44	333.24												
3/4	1,047.95	686.92	325.72												
6	1,040.44	679.39	318.19												
1/4	1,032.94	671.87	310.67												
1/2	1,025.44	664.34	303.14												
3/4	1,017.93	656.82	295.62												
7	1,010.43	649.29	288.09												
1/4	1,002.92	641.77	280.57												
1/2	995.42	634.24	273.04												
3/4	987.92	626.72	265.52												
8	980.39	619.19	258.17												
1/4	972.87	611.67	250.82												
1/2	965.34	604.14	243.47												
3/4	957.82	596.62	236.12												
9	950.29	589.09	228.78												
1/4	942.77	581.57	221.43												
1/2	935.24	574.04	214.08												
3/4	927.72	566.52	206.73												
10	920.19	558.99	199.38												
1/4	912.67	551.47	192.04												
1/2	905.14	543.94	184.69												
3/4	897.62	536.42	177.34												
11	890.09	528.89	169.99												
1/4	882.57	521.37	162.64												
1/2	875.04	513.84	155.30												
3/4	867.52	506.32	147.95												

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 12/16/08

* CAPACITY BELOW STRIKE POINT.

REFERENCE GAUGE HEIGHT : 18'-4 3/4" (TO RIM OF 2" DIA. BALL VALVE
LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE
IN ACCORDANCE WITH APPLICABLE API STANDARDS AND
ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION